

Aluminum Electrolytic Capacitors



三泰 科技有限公司
Suntan Technology Company Limited

(Suntan Capacitors Company 三泰電容器公司)

Unit 1, 4/F., Dormind Industrial Building, 13 Yip Fung Street, Fanling, N.T., Hong Kong
E-mail: info@suntan.com.hk URL: www.suntan.com.hk Tel: (852) 8202 8782 Fax: (852) 8208 6246


TS13DA CD50BP

- 5mm height, Non-Polarized
- Bi-polar
- Radial
- -40 ~ +85°C
- 6.3 ~ 50V
- 0.1 ~ 47uF
- 1000 hours


TS13DC CD70H

- 105°C, 7mm height
- Radial
- -55 ~ +105°C
- 6.3 ~ 50V
- 0.1 ~ 100uF
- 1000 hours


TS13DB CD50H

- 105°C, 5mm height
- Radial
- -55 ~ +105°C
- 6.3 ~ 50V
- 0.1 ~ 100uF
- 1000 hours


TS13DS CD50S

- 85°C, 5mm height
- Radial
- -40 ~ +85°C
- 4 ~ 50V
- 0.1 ~ 470uF
- 1000 hours


TS13DT CD11C

- 85°C, 7mm height
- Radial
- -40 ~ +85°C
- 4 ~ 100V
- 0.1 ~ 330uF
- 1000 hours


TS13DD CD71C

- 7mm height, Bi-polar
- Radial
- -40 ~ +85°C
- 6.3 ~ 50V
- 0.1 ~ 47uF
- 1000 hours


TS13

- General & Miniature
- Radial
- -40 ~ +85°C
- 4 ~ 400V
- 0.1 ~ 10,000uF
- 1000 hours


TS13DE CD110X

- General, Super Miniaturized
- Radial
- -40 ~ +85°C
- 6.3 ~ 450V
- 0.1 ~ 22,000uF
- 2000 hours


TS13D1 CD81

- 105°C, Low Leakage
- Radial
- -40 ~ +105°C
- 10 ~ 250V
- 0.1 ~ 6800uF
- 2000 hours


TS13DK CD265

- 125°C, 1000hours
- Radial
- -40 ~ +125°C
- 10 ~ 100V
- 0.47 ~ 1,000uF
- 1000 hours


TS13DO CD171

- For Photo Flash
- Radial
- -20 ~ +85°C
- 330V
- 80 ~ 300uF


TS13DJ CD287

- 105°C, Extra Low Impedance, Long Life
- Radial
- -55 ~ +105°C
- 6.3 ~ 100V
- 0.47 ~ 15,000uF
- 5000 hours


TS13DG CD263

- 105°C, General switching power supplies
- Radial
- -40 ~ +105°C / -25 ~ +105°C
- 6.3 ~ 100V / 160 ~ 400V
- 0.1 ~ 15,000uF / 0.47 ~ 220uF
- 2000 hours


TS13DH CD264

- 105°C, Ballast, Power Supply, Long Life
- Radial
- -40 ~ +105°C / -25 ~ +105°C
- 160 ~ 250V / 350 ~ 450V
- 4.7 ~ 220uF / 1 ~ 47uF
- 3000hours


TS13DI CD286

- 105°C, Extra Low Impedance
- Radial
- -55 ~ +105°C
- 6.3 ~ 100V
- 0.47 ~ 15,000uF
- 2000 hours


TS13DF CD71

- Non - Polarized
- Radial
- -40 ~ +85°C
- 6.3 ~ 160V
- 0.47 ~ 6,800uF
- 1000 hours


TS13DN CD71S

- For Horizontal Deflection
- Radial
- -55 ~ +105°C
- 50V
- 2.2 ~ 15uF
- 1000 hours


TS13DL CD117

- Low Leakage Current
- Radial
- -40 ~ +85°C
- 6.3 ~ 50V
- 0.47 ~ 2,200uF
- 1000 hours


TS13DM CD71A

- For Speaker Network
- Radial
- -40 ~ +85°C
- 50V
- 1 ~ 100uF
- 1000hours


TS14

- High Temperature
- Radial
- -40 ~ +105°C
- 6.3 ~ 400V
- 0.1 ~ 15,000uF / 0.1 ~ 10,000uF
- 2000hours



TS13D9 CD11G

- For Ballast & Save Lamp - 3000 hours
- Radial
- -40 ~ +105°C / -25 ~ 105°C
- 200 ~ 250V / 350 ~ 450V
- 1.0 ~ 220uF
- 3000 hours

TS13D8 CD11GH

- For Ballast & Save Lamp - 5000 hours
- Radial
- -40 ~ +105°C / -25 ~ 105°C
- 200 ~ 250V / 350 ~ 450V
- 1.0 ~ 150uF
- 5000 ~ 8000 hours

TS13D4 CD11GA

- For Ballast & Save Lamp - 8000 hours
- Radial
- -40 ~ +105°C / -25 ~ 105°C
- 200 ~ 250V / 350 ~ 450V
- 1.0 ~ 150uF
- 2000 / 8000 hours

TS13D2 CD11GE

- For Ballast & Save Lamp - 10000 hours
- Radial
- -40 ~ 105°C / -25 ~ 105°C
- 160 ~ 250V / 350 ~ 450V
- 1.0 ~ 150uF
- 8,000 ~ 10,000 hours

TS13DP CD293

- For Speaker Network
- Snap-in
- -40 ~ +85°C / -25 ~ +85°C
- 10 ~ 400V / 450V
- 68 ~ 22,000uF
- 2000 hours



TS13DQ CD295

- General, Miniaturized, Long Life
- Snap-in
- -40 ~ +85°C
- 10 ~ 450V
- 68 ~ 22,000uF
- 5000 hours

TS13DR CD294

- 105°C, Miniaturized
- Snap-in
- -40 ~ +105°C
- 10 ~ 400V
- 39 ~ 22,000uF
- 2000hours

TS13DS CD296

- 105°C, Miniaturized, Long Life
- Snap-in
- -40 ~ +105°C
- 10 ~ 400V
- 39 ~ 22,000uF
- 3000 hours

TS13D0 CD297

- 105°C, 5000 hours
- Snap-in
- -40 ~ +105°C
- 10 ~ 450V
- 68 ~ 56,000uF

TS13DW CDPC

- For P.F.C. Circuit
- Snap-in, Lug
- -25 ~ +85°C
- 250 / 400V
- 100 ~ 440uF / 45 ~ 220uF
- 2000 hours



TS13DX CD135

- General, Miniaturized
- Screw
- -40 ~ +85°C
- 10 ~ 450V
- 270 ~ 820,000uF
- 2000 hours

TS13DY CD136

- 105°C, Long Life
- Screw
- -40 ~ +105°C / -25 ~ +105°C
- 10 ~ 100V / 160 ~ 400V
- 180 ~ 680,000 uF
- 2000 hours

TS13DZ CD138

- General, Long Life
- Screw
- -40 ~ +85°C
- 350 / 450V
- 1,000 ~ 18,000uF
- 5000 hours

TS13EF CD13L

- 85°C, Extra Long Life
- For Inverter
- Screw
- -40 ~ +85°C
- 350 / 400 / 450V
- 1,000 ~ 15,000uF
- 20,000 hours

TS13EG CD135X

- 85°C, 2000 hours
- Screw
- -40 ~ +85°C
- 400 / 450 / 500V
- 1,200 ~ 22,000uF



TS13EH CD137

- 85°C, Long Life
- For Inverter
- Screw
- -40 ~ +85°C
- 400 / 450 / 500 / 550V
- 1,000 ~ 22,000uF
- 5000 hours

TS13EI CD139

- 105°C, For Inverter
- Screw
- -40 ~ +105°C
- 350 / 400 / 450V
- 1,000 ~ 15,000uF
- 5000 hours

TS13DT CD13

- 85°C, Miniaturized
- Lug
- -40 ~ +85°C / -25 ~ +85°C
- 16 ~ 450V
- 33 ~ 68,000uF
- 1000 hours

TS13DU CD17

- For Photo Flash
- Lug
- -20 ~ +55°C
- 330 / 360VV, DC
- 150 ~ 1,500uF

TS13DV CDIN

- For Air Conditioner
- Higher Ripple Current
- Lug
- -25 ~ +85°C
- 400~450V
- 1,000~2,400uF
- 2000 hours


TS13D3 CD60

- ♦ For Motor Starting
- ♦ Lug
- ♦ -20 ~ +70°C
- ♦ 110 ~ 330V.AC
- ♦ 25 ~ 500uF
- ♦ 75,000 & 30,000 times


TS13AE

- ♦ 85°C, Low Voltage, 2 Rubber type
- ♦ Axial
- ♦ -40 ~ +85°C
- ♦ 6.3 ~ 160V
- ♦ 3.3 ~ 22,000uF
- ♦ 2000 hours


TS13AD

- ♦ 85°C, Low Leakage, 2 Rubber type
- ♦ Axial
- ♦ -40 ~ +85°C
- ♦ 6.3 ~ 160V
- ♦ 3.3 ~ 22,000uF
- ♦ 2000 hours


TS13C0

- ♦ Standard
- ♦ SMD-Chip
- ♦ -40 ~ +85°C
- ♦ 4 ~ 100V
- ♦ 0.1 ~ 10,000uF
- ♦ 2000 hours


TS13C1

- ♦ Wide Temperature
- ♦ SMD - Chip
- ♦ -55 ~ +105°C
- ♦ 4 ~ 100V
- ♦ 0.1 ~ 10,000uF
- ♦ 1000 ~ 2000 hours


TS13C2

- ♦ Non-Polarized
- ♦ SMD-Chip
- ♦ -40 ~ +85°C
- ♦ 6.3 ~ 50V
- ♦ 0.1 ~ 100uF
- ♦ 1000 hours


TS13C3

- ♦ Non-Polarized, 105°C
- ♦ SMD - Chip
- ♦ -55 ~ +105°C
- ♦ 6.3 ~ 50V
- ♦ 0.1 ~ 47uF
- ♦ 1000 hours


TS13C4

- ♦ Low Impedance
- ♦ SMD - Chip
- ♦ -55 ~ +105°C
- ♦ 6.3 ~ 50V
- ♦ 1 ~ 6,800uF
- ♦ 2000 hours


TS13C5

- ♦ Extra Low Impedance
- ♦ SMD - Chip
- ♦ -55 ~ +105°C
- ♦ 6.3 ~ 50V
- ♦ 4.7 ~ 6,800uF
- ♦ 3000 hours


TS13C6

- ♦ Long Life Assurance
- ♦ SMD - Chip
- ♦ -55 ~ +105°C
- ♦ 6.3 ~ 50V
- ♦ 0.1 ~ 4700uF
- ♦ 3000 hours


TS13C7

- ♦ 5000 hours Load Life
- ♦ SMD - Chip
- ♦ -55 ~ +105°C
- ♦ 6.3 ~ 100V
- ♦ 0.1 ~ 4,700 uF
- ♦ 5000 hours


TS13C8

- ♦ High Reliability
- ♦ SMD - Chip
- ♦ -40 ~ +125°C
- ♦ 10 ~ 450V
- ♦ 3.3 ~ 2,200uF
- ♦ 5000 hours


TS13C9

- ♦ Low Leakage
- ♦ SMD - Chip
- ♦ -40 ~ +85°C
- ♦ 6.3 ~ 50V
- ♦ 0.1 ~ 220uF
- ♦ 2000 hours


TS13CA

- ♦ Super Low Impedance
- ♦ SMD - Chip
- ♦ -55 ~ +105°C
- ♦ 6.3 ~ 100V
- ♦ 3.3 ~ 6,800uF
- ♦ 2000-5000 hours


TS13CC

- ♦ Mid-To-High Voltage
- ♦ SMD-Chip
- ♦ -40 ~ +125°C
- ♦ 160 ~ 450V
- ♦ 3.3 ~ 68uF
- ♦ 5000 hours


TS12

- ♦ Electric Double Layer Capacitor
- ♦ -25 ~ +70°C
- ♦ 2.4 ~ 6.3V
- ♦ 0.033 ~ 1F
- ♦ 1000 hours


TS12S-M

- ♦ Electric Double Layer Capacitor - Radial / Snap-in - Low Leakage
- ♦ -25 ~ +70°C
- ♦ 2.5VDC
- ♦ 0.7 ~ 8.0F
- ♦ 1000 hours


TS12S-R

- ♦ Electric Double Layer Capacitor - Radial / Snap-in
- ♦ -40 ~ +70°C
- ♦ 2.5VDC
- ♦ 0.7 ~ 120F
- ♦ 1000 hours


TS12S-S

- ♦ Electric Double Layer Stacked Coin
- ♦ -25 ~ +70°C
- ♦ 2.7 ~ 5.5V
- ♦ 0.15 ~ 8.0F
- ♦ 1000 hours


TS12SV

- ♦ Electric Double Layer Serial Structure
- ♦ -25 ~ +70°C
- ♦ 5.0 / 5.5 V
- ♦ 0.33 ~ 4.0F
- ♦ 1000 hours