

METALLIZED POLYPROPYLENE FILM CAPACITOR-X2

Professional Manufacturer Since 1978

Class X2 Safety Capacitor — TS08S

SPECIFICATIONS:


- VOLTAGE RATING : 250/275/305/310 VAC
- CAPACITANCE RANGE : 0.001 - 2.2 μ F
- CAPACITANCE TOLERANCE : $\pm 10\%$ std
- OPERATING TEMPERATURE : -40°C to +110°C
- TESTING VOLTAGE : 4.3UR DC/5s
- DISSIPATION FACTOR : $\text{tg}\delta \leq 0.0010$
- INSULATION RESISTANCE : I.R. $\geq 15,000\text{M}\Omega$ (C < 0.33 μ F)
I.R. $\geq 6,000\text{M}\Omega$ (C ≥ 0.33 μ F)



FEATURES:

- AC-Capacitors
- Class X2 safety capacitors
- Reliable self-healing
- Metallized polypropylene
- Low self inductance
- RoHS directive compliant
- Low ESR
- Small size
- Ammo Tape Pack, Cut leads, Long leads are available
- Interference suppression capacitor with VDE, ENEC and UL approvals

DRAWINGS:



CERTIFICATIONS:

	LOGO MARK	COUNTRY	APPROVAL STANDARD	APPROVAL NO.	CLASS	CAP.RANGE	RATED VOLTAGE
CUL,UL		CANADA/U.S.A	UL/IEC 60384-14	E344971	X2	0.001 μ F to 2.2 μ F	250/275/305/310VAC
VDE		GERMANY	DIN EN 60384-14 (VDE 0565 Teil 1-1)	40035433	X2	0.001 μ F to 2.2 μ F	275/305/310VAC
ENEC		EUROPE	EN 60384-14; IEC 60384-14	40035433	X2	0.001 μ F to 2.2 μ F	275/305/310VAC

三泰 科技有限公司
Suntan Technology Company Limited

METALLIZED POLYPROPYLENE FILM CAPACITOR-X2

Professional Manufacturer Since 1978

Class X2 Safety Capacitor — TS08S

APPLICATIONS:

- ◆ Line - By - Pass Components
- ◆ Across - The - Line Capacitors
- ◆ Antenna-Coupling Components
- ◆ Electromagnetic Interference (EMI) Filters



DIMENSIONS:

(Unit : mm)

CAP	A type 275VAC					A type 305VAC					A type 310VAC				
	L±1.0	T±1.0	H±1.0	P±1.0	dΦ±0.05	L±1.0	T±1.0	H±1.0	P±1.0	dΦ±0.05	L±1.0	T±1.0	H±1.0	P±1.0	dΦ±0.05
0.001	13.0	5.0	11.0	10.0	0.6										
0.0022	13.0	5.0	11.0	10.0	0.6	13.0	5.0	11.0	10.0	0.6	13.0	5.0	11.0	10.0	0.6
0.0027	13.0	5.0	11.0	10.0	0.6	13.0	5.0	11.0	10.0	0.6	13.0	5.0	11.0	10.0	0.6
0.0033	13.0	5.0	11.0	10.0	0.6	13.0	5.0	11.0	10.0	0.6	13.0	5.0	11.0	10.0	0.6
0.0039	13.0	5.0	11.0	10.0	0.6	13.0	5.0	11.0	10.0	0.6	13.0	5.0	11.0	10.0	0.6
0.0047	13.0	5.0	11.0	10.0	0.6	13.0	5.0	11.0	10.0	0.6	13.0	5.0	11.0	10.0	0.6
0.0056	13.0	5.0	11.0	10.0	0.6	13.0	5.0	11.0	10.0	0.6	13.0	5.0	11.0	10.0	0.6
0.0068	13.0	5.0	11.0	10.0	0.6	13.0	5.0	11.0	10.0	0.6	13.0	5.0	11.0	10.0	0.6
0.0082	13.0	5.0	11.0	10.0	0.6	13.0	5.0	11.0	10.0	0.6	13.0	5.0	11.0	10.0	0.6
0.01	13.0	5.0	11.0	10.0	0.6	13.0	5.0	11.0	10.0	0.6	13.0	5.0	11.0	10.0	0.6
0.012	13.0	5.0	11.0	10.0	0.6	13.0	5.0	11.0	10.0	0.6	13.0	5.0	11.0	10.0	0.6
0.015	13.0	5.0	11.0	10.0	0.6	13.0	5.0	11.0	10.0	0.6	13.0	5.0	11.0	10.0	0.6
0.018	13.0	5.0	11.0	10.0	0.6	13.0	5.0	11.0	10.0	0.6	13.0	5.0	11.0	10.0	0.6
0.022	13.0	5.0	11.0	10.0	0.6	13.0	5.0	11.0	10.0	0.6	13.0	5.0	11.0	10.0	0.6
0.027	18.0	5.0	11.0	15.0	0.6	18.0	5.0	11.0	15.0	0.6	18.0	5.0	11.0	15.0	0.6
0.033	13.0	5.0	11.0	10.0	0.6	13.0	5.0	11.0	10.0	0.6	13.0	5.0	11.0	10.0	0.6
0.039	13.0	5.0	11.0	10.0	0.6	13.0	5.0	11.0	10.0	0.6	13.0	5.0	11.0	10.0	0.6
0.047	18.0	5.0	11.0	15.0	0.6	18.0	5.0	11.0	15.0	0.6	18.0	5.0	11.0	15.0	0.6
0.056	18.0	5.0	11.0	15.0	0.6	18.0	5.0	11.0	15.0	0.6	18.0	5.0	11.0	15.0	0.6
0.068	18.0	5.0	11.0	15.0	0.6	18.0	5.0	11.0	15.0	0.6	18.0	5.0	11.0	15.0	0.6
0.082	18.0	6.0	12.0	15.0	0.6	18.0	6.0	12.0	15.0	0.6	18.0	6.0	12.0	15.0	0.6
0.1	18.0	6.0	12.0	15.0	0.8	18.0	6.0	12.0	15.0	0.8	18.0	6.0	12.0	15.0	0.8
0.12	18.0	7.5	13.5	15.0	0.8	18.0	7.5	13.5	15.0	0.8	18.0	7.5	13.5	15.0	0.8
0.15	18.0	7.5	13.5	15.0	0.8	18.0	7.5	13.5	15.0	0.8	18.0	7.5	13.5	15.0	0.8
0.15	26.5	7.0	16.5	22.5	0.8	26.5	7.0	16.5	22.5	0.8	26.5	7.0	16.5	22.5	0.8
0.18	26.5	7.0	16.5	22.5	0.8	26.5	7.0	16.5	22.5	0.8	26.5	7.0	16.5	22.5	0.8
0.22	26.5	7.0	16.5	22.5	0.8	26.5	7.0	16.5	22.5	0.8	26.5	7.0	16.5	22.5	0.8
0.27	26.5	7.0	16.5	22.5	0.8	26.5	7.0	16.5	22.5	0.8	26.5	7.0	16.5	22.5	0.8
0.33	26.5	7.0	16.5	22.5	0.8	26.5	7.0	16.5	22.5	0.8	26.5	7.0	16.5	22.5	0.8
0.47	26.5	10.0	19.0	22.5	0.8	26.5	10.0	19.0	22.5	0.8	26.5	10.0	19.0	22.5	0.8
0.47	31.5	10.8	19.5	27.5	0.8	31.5	10.8	19.5	27.5	0.8	31.5	10.8	19.5	27.5	0.8
0.56	31.5	10.8	19.5	27.5	0.8	31.5	10.8	19.5	27.5	0.8	31.5	10.8	19.5	27.5	0.8
0.68	31.5	10.8	19.5	27.5	0.8	31.5	10.8	19.5	27.5	0.8	31.5	10.8	19.5	27.5	0.8
0.82	31.5	10.8	19.5	27.5	0.8	31.5	10.8	19.5	27.5	0.8	31.5	10.8	19.5	27.5	0.8
1.0	31.5	13.0	22.0	27.5	0.8	31.5	13.0	22.0	27.5	0.8	31.5	13.0	22.0	27.5	0.8
1.5	31.5	13.0	22.0	27.5	0.8	31.5	13.0	22.0	27.5	0.8	31.5	13.0	22.0	27.5	0.8
2.2	31.5	13.0	22.0	27.5	0.8	31.5	14.0	25.0	27.5	0.8	31.5	14.0	25.0	27.5	0.8
CAP	B type 275VAC					B type 305VAC					B type 310VAC				
	L±1.0	T±1.0	H±1.0	P±1.0	dΦ±0.05	L±1.0	T±1.0	H±1.0	P±1.0	dΦ±0.05	L±1.0	T±1.0	H±1.0	P±1.0	dΦ±0.05
0.047	13.0	5.0	11.0	10.0	0.6	13.0	5.0	11.0	10.0	0.6	13.0	5.0	11.0	10.0	0.6
0.056	13.0	6.0	12.0	10.0	0.6	13.0	6.0	12.0	10.0	0.6	13.0	6.0	12.0	10.0	0.6
0.068	13.0	6.0	12.0	10.0	0.6	13.0	6.0	12.0	10.0	0.6	13.0	6.0	12.0	10.0	0.6
0.082	13.0	6.0	12.0	10.0	0.6	13.0	6.0	12.0	10.0	0.6	13.0	6.0	12.0	10.0	0.6
0.1	13.0	6.0	12.0	10.0	0.8	13.0	6.0	12.0	10.0	0.8	13.0	6.0	12.0	10.0	0.8
0.18	18.0	7.5	13.5	15.0	0.8	18.0	7.5	13.5	15.0	0.8	18.0	7.5	13.5	15.0	0.8
0.22	18.0	8.5	14.5	15.0	0.8	18.0	8.5	14.5	15.0	0.8	18.0	8.5	14.5	15.0	0.8
0.27	18.0	10.0	15.8	15.0	0.8	18.0	10.0	15.8	15.0	0.8	18.0	10.0	15.8	15.0	0.8
0.33	18.0	10.0	15.8	15.0	0.8	18.0	10.0	15.8	15.0	0.8	18.0	10.0	15.8	15.0	0.8
0.47	18.0	11.0	19.0	15.0	0.8	18.0	11.0	19.0	15.0	0.8	18.0	11.0	19.0	15.0	0.8
0.56	26.5	10.0	19.0	22.5	0.8	26.5	10.0	19.0	22.5	0.8	26.5	10.0	19.0	22.5	0.8
0.68	26.5	10.0	19.0	22.5	0.8	26.5	10.0	19.0	22.5	0.8	26.5	10.0	19.0	22.5	0.8
0.82	26.5	10.0	19.0	22.5	0.8	26.5	10.0	19.0	22.5	0.8	26.5	10.0	19.0	22.5	0.8
1.0	26.5	10.0	19.0	22.5	0.8	26.5	11.0	20.0	22.5	0.8	26.5	11.0	20.0	22.5	0.8
1.5						26.5	13.0	22.0	22.5	0.8	26.5	13.0	22.0	22.5	0.8

Please contact us for special item or size not listed.

Please visit our website to get more update data, those data & specification are subject to change without notice.